

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Detail King STS+ Paint Sealant

Version number: GHS 3.0
Replaces version of: 2025-11-14 (GHS 2)

Revision: 2025-12-15

SECTION 1: Identification

1.1 Product identifier

Trade name

Detail King STS+ Paint Sealant

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Paint sealer with resin

Professional use

Industrial use

Consumer use (private households)

3405.30.00.

1.3 Details of the supplier of the safety data sheet

Detail King
947A Old Frankstown Road
Pittsburgh, PA 15239

1-724-325-0008
support@detailking.com

1.4 Emergency telephone number

Emergency information service

USA 1.800.535.5053, INTL 1.352.323.3500
24 hour emergency number

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
A.10	aspiration hazard	1	Asp. Tox. 1	H304

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The mixture contains a substance that was identified as a PBT (persistent, bioaccumulative and toxic). The mixture contains a substance that was identified as vPvB (very persistent and very bioaccumulative).

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS08



- Hazard statements

H304

May be fatal if swallowed and enters airways.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Detail King STS+ Paint Sealant

Version number: GHS 3.0
Replaces version of: 2025-11-14 (GHS 2)

Revision: 2025-12-15

- Precautionary statements

P301+P310 If swallowed: Immediately call a poison center/doctor.
P331 Do NOT induce vomiting.
P405 Store locked up.
P501 Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling

odorless mineral spirits, distillates (petroleum)
hydrotreated, light, Naphtha (petroleum), hydro-
treated light, heptane

2.3 Other hazards

Special danger of slipping by leaking/spilling product.

Results of PBT and vPvB assessment

Contains a PBT-substance at a concentration of $\geq 0.1\%$. Contains a vPvB-substance at a concentration of $\geq 0.1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
odorless mineral spirits	CAS No 64742-48-9	5 – < 12	Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
China Clay, calcined	CAS No 66402-68-4	5 – < 12	Acute Tox. 4 / H332
distillates (petroleum) hydro- treated, light	CAS No 64742-47-8	5 – < 12	Asp. Tox. 1 / H304
decamethylcyclpentasiloxane	CAS No 541-02-6	1 – < 5	Flam. Liq. 4 / H227
1,2-benzothiazol-3-one	CAS No 2634-33-5	< 0.1	Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Eye Dam. 1 / H318 Skin Sens. 1 / H317

Hazardous ingredients, Consideration of other advice

This table, if present, includes all GHS classified ingredients present above their cut-off limits, even if the finished product is not classified as hazardous by GHS.

Exact percentage of ingredients is withheld as a trade secret.

Remarks

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Detail King STS+ Paint Sealant

Version number: GHS 3.0
Replaces version of: 2025-11-14 (GHS 2)

Revision: 2025-12-15

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Detail King STS+ Paint Sealant

Version number: GHS 3.0
Replaces version of: 2025-11-14 (GHS 2)

Revision: 2025-12-15

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation
Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Control of the effects

Protect against external exposure, such as
frost

- Packaging compatibilities
Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	petroleum distillates (naphtha) (rubber solvent)	64742-48-9	PEL	500	2,000						29 CFR 1910.1000

Notation

Ceiling-C	ceiling value is a limit value above which exposure should not occur
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
China Clay, calcined	66402-68-4	DNEL	16 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
decamethylcyclopentasiloxane	541-02-6	DNEL	97 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
decamethylcyclopentasiloxane	541-02-6	DNEL	24 mg/m ³	human, inhalatory	worker (industry)	acute - local effects

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Detail King STS+ Paint Sealant

Version number: GHS 3.0
Replaces version of: 2025-11-14 (GHS 2)

Revision: 2025-12-15

Relevant DNELs of components

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
decamethylcyclopentasiloxane	541-02-6	DNEL	97 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
decamethylcyclopentasiloxane	541-02-6	DNEL	24 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
1,2-benzothiazol-3-one	2634-33-5	DNEL	6.8 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
1,2-benzothiazol-3-one	2634-33-5	DNEL	0.97 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components

Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
decamethylcyclopentasiloxane	541-02-6	PNEC	10 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	11 mg/kg	benthic organisms	sediment	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	13 mg/kg	(top) predators	water	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	1.1 mg/kg	pelagic organisms	sediment	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	1.2 µg/l	aquatic organisms	freshwater	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	0.12 µg/l	aquatic organisms	marine water	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	11 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	1.1 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	2.5 mg/kg	terrestrial organisms	soil	short-term (single instance)
1,2-benzothiazol-3-one	2634-33-5	PNEC	4 µg/l	aquatic organisms	freshwater	short-term (single instance)
1,2-benzothiazol-3-one	2634-33-5	PNEC	0.4 µg/l	aquatic organisms	marine water	short-term (single instance)
1,2-benzothiazol-3-one	2634-33-5	PNEC	1 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
1,2-benzothiazol-3-one	2634-33-5	PNEC	50 µg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
1,2-benzothiazol-3-one	2634-33-5	PNEC	5 µg/kg	aquatic organisms	marine sediment	short-term (single instance)
1,2-benzothiazol-3-one	2634-33-5	PNEC	3 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Detail King STS+ Paint Sealant

Version number: GHS 3.0
Replaces version of: 2025-11-14 (GHS 2)

Revision: 2025-12-15

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid (viscous)
Color	off-white
Odor	coconut
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	100 °C
Flammability	this material is combustible, but will not ignite readily
Lower and upper explosion limit	0.6 vol% - 7.6 vol%
Flash point	>97 °C at 101 kPa >207 °F at 760 mmHg closed cup
Auto-ignition temperature	262 °C (auto-ignition temperature (liquids and gases))
Decomposition temperature	not relevant
pH (value)	6 – 7 (25 °C)
Kinematic viscosity	not determined
Solubility(ies)	not determined

Partition coefficient

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Detail King STS+ Paint Sealant

Version number: GHS 3.0
Replaces version of: 2025-11-14 (GHS 2)

Revision: 2025-12-15

Vapor pressure	32 hPa at 25 °C
----------------	-----------------

Density and/or relative density

Density	1.1 g/cm ³ at 20 °C
Relative vapour density	information on this property is not available

Particle characteristics	not relevant (liquid)
--------------------------	-----------------------

Information with regard to physical hazard classes	hazard classes acc. to GHS (physical hazards): not relevant
--	--

Other safety characteristics

Temperature class (USA, acc. to NEC 500)	T2B (maximum permissible surface temperature on the equipment: 260°C)
--	---

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Detail King STS+ Paint Sealant

Version number: GHS 3.0
Replaces version of: 2025-11-14 (GHS 2)

Revision: 2025-12-15

Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ATE
China Clay, calcined	66402-68-4	oral	>2,000 mg/kg
China Clay, calcined	66402-68-4	dermal	>2,500 mg/kg
China Clay, calcined	66402-68-4	inhalation: dust/mist	>2.3 mg/l/4h
decamethylcyclopentasiloxane	541-02-6	dermal	>2,000 mg/kg
decamethylcyclopentasiloxane	541-02-6	inhalation: dust/mist	8.7 mg/l/4h
1,2-benzothiazol-3-one	2634-33-5	oral	670 mg/kg
1,2-benzothiazol-3-one	2634-33-5	dermal	>2,000 mg/kg

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Contains 1,2-benzothiazol-3-one. May produce an allergic reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
odorless mineral spirits	64742-48-9	LL50	8.2 mg/l	fish	96 h
odorless mineral spirits	64742-48-9	EL50	4.5 mg/l	aquatic invertebrates	48 h
decamethylcyclopentasiloxane	541-02-6	LC50	>16 µg/l	rainbow trout (Oncorhynchus mykiss)	96 h
decamethylcyclopentasiloxane	541-02-6	EC50	>2.9 µg/l	daphnia magna	48 h
1,2-benzothiazol-3-one	2634-33-5	LC50	17 mg/l	fish	96 h

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Detail King STS+ Paint Sealant

Version number: GHS 3.0
Replaces version of: 2025-11-14 (GHS 2)

Revision: 2025-12-15

Aquatic toxicity (acute) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
1,2-benzothiazol-3-one	2634-33-5	EC50	2.9 mg/l	aquatic invertebrates	48 h
1,2-benzothiazol-3-one	2634-33-5	ErC50	150 µg/l	algae	72 h

Aquatic toxicity (chronic) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
China Clay, calcined	66402-68-4	EC50	300 mg/l	microorganisms	3 h
odorless mineral spirits	64742-48-9	EL50	10 mg/l	fish	21 d
odorless mineral spirits	64742-48-9	EC50	15 mg/l	microorganisms	40 h
decamethylcyclopentasiloxane	541-02-6	LC50	>16 µg/l	rainbow trout (Oncorhynchus mykiss)	14 d
decamethylcyclopentasiloxane	541-02-6	EC50	>15 µg/l	daphnia magna	21 d
1,2-benzothiazol-3-one	2634-33-5	EC50	13 mg/l	microorganisms	3 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Contains a PBT-substance at a concentration of $\geq 0.1\%$. Contains a vPvB-substance at a concentration of $\geq 0.1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Detail King STS+ Paint Sealant

Version number: GHS 3.0
Replaces version of: 2025-11-14 (GHS 2)

Revision: 2025-12-15

SECTION 14: Transport information

14.1 UN number

DOT	UN 3082
IMDG-Code	UN 3082
ICAO-TI	UN 3082

14.2 UN proper shipping name

DOT	Environmentally hazardous substance, liquid, n.o.s.
IMDG-Code	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
ICAO-TI	Environmentally hazardous substance, liquid, n.o.s.
Technical name (hazardous ingredients)	decamethylcyclopentasiloxane, odorless mineral spirits

14.3 Transport hazard class(es)

DOT	9
IMDG-Code	9
ICAO-TI	9

14.4 Packing group

DOT	III
IMDG-Code	III
ICAO-TI	III

14.5 Environmental hazards

	hazardous to the aquatic environment
Environmentally hazardous substance (aquatic environment)	decamethylcyclopentasiloxane, odorless mineral spirits

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Not regulated under DOT until packaged in single containers larger than 119 gallons each - liquid, or 882 lbs each - solid.

Particulars in the shipper's declaration	UN3082, Environmentally hazardous substance, liquid, n.o.s., (contains: decamethylcyclopentasiloxane, odorless mineral spirits), 9, III
Reportable quantity (RQ)	226,040 lbs (102,622 kg) (diethanolamine) (methanol)
Danger label(s)	9, fish and tree



Environmental hazards	yes (hazardous to the aquatic environment)
-----------------------	--

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Detail King STS+ Paint Sealant

Version number: GHS 3.0
Replaces version of: 2025-11-14 (GHS 2)

Revision: 2025-12-15

Special provisions (SP) 8, 146, 173, 335, 441, IB3, T4, TP1, TP29

ERG No 171

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant yes (hazardous to the aquatic environment) (odorless mineral spirits)

Danger label(s) 9, fish and tree



Special provisions (SP) 274, 335, 375, 969

Excepted quantities (EQ) E1

Limited quantities (LQ) 5 L

EmS F-A, S-F

Stowage category A

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Environmental hazards yes (hazardous to the aquatic environment)

Danger label(s) 9, fish and tree



Special provisions (SP) A97, A158, A197, A215

Excepted quantities (EQ) E1

Limited quantities (LQ) 30 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) all ingredients are listed (ACTIVE) or exempt from listing

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
water	7732-18-5	solvent	
odorless mineral spirits	64742-48-9	solvents	Canada PBiTs EC Annex VI CMRs - Cat. 1B
China Clay, calcined	66402-68-4	abrasive	
distillates (petroleum) hydrotreated, light	64742-47-8	solvents	

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Detail King STS+ Paint Sealant

Version number: GHS 3.0
Replaces version of: 2025-11-14 (GHS 2)

Revision: 2025-12-15

Name of substance	CAS No	Functionality	Authoritative Lists
polydimethylsiloxane	63148-62-9	surface modifier	
decamethylcyclopentasiloxane	541-02-6	solvents	Canada PBiTs CECBP - Priority Chemicals EC PBTs
polytrimethylhydrosilylsiloxane	68988-56-7	surface modifier	
trimethylsiloxysilicate	68988-56-7	resin	
N,N-bis(2-Hydroxyethyl)oleamide	93-83-4	surfactant	
methyl alkyl (C25-54, branched and linear) siloxane	189378-12-9	surface modifier	
organically modified hectorite	12001-31-9	viscosity modifier	
1-alkenes, C24-54 (branched and linear)	131459-42-2	solvents	
ethyl alcohol	64-17-5	alcohols	
tetra(trimethylsiloxy)silane	3555-47-3	surface modifier	Canada PBiTs
2,2'-iminodiethanol	111-42-2	impurity	CA TACs IARC Carcinogens - 2B OEHHA RELs Prop 65
coumarin	91-64-5	fragrance	EU Fragrance Allergens
benzyl benzoate	120-51-4	fragrance	EU Fragrance Allergens
1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran	1222-05-5		EU Fragrance Allergens
Polyethylene glycol	25322-68-3	surfactant	
1,2-benzothiazol-3-one	2634-33-5	preservative	

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
odorless mineral spirits	64742-48-9	A, O	

Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals					
Name of substance	Name acc. to inventory	CAS No	Wt%	Remarks	Type of the toxicity
methanol	methanol	67-56-1	0.0055		developmental
ethyl alcohol	ethanol (ethyl alcohol)	64-17-5	0.1	in alcoholic beverages	developmental
4-methylpentan-2-one	methyl isobutyl ketone	108-10-1	0.00077		cancer
4-methylpentan-2-one	methyl isobutyl ketone (MIBK)	108-10-1	0.00077		developmental

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Detail King STS+ Paint Sealant

Version number: GHS 3.0
Replaces version of: 2025-11-14 (GHS 2)

Revision: 2025-12-15

Proposition 65 List of chemicals

Name of substance	Name acc. to inventory	CAS No	Wt%	Remarks	Type of the toxicity
					mental
2,2'-iminodiethanol	diethanolamine	111-42-2	0.044		cancer

VOC content

- Regulated Volatile Organic Compounds (VOC-EPA) 7.9 %
- Regulated Volatile Organic Compounds (VOC-Cal ARB) 7.9 %

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	/	none
Health	0	no significant risk to health
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	0	material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
CA	DSL	not all ingredients are listed
CA	NDSL	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)
AU	AIIC	not all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Detail King STS+ Paint Sealant

Version number: GHS 3.0
Replaces version of: 2025-11-14 (GHS 2)

Revision: 2025-12-15

Country	Inventory	Status
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	not all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NDSL	Non-domestic Substances List (NDSL)
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
1.2	Relevant identified uses: Paint sealer with resin Professional use Industrial use Consumer use (private households)	Relevant identified uses: Paint sealer with resin Professional use Industrial use Consumer use (private households)3405.30.00.	yes
1.2	HS code: 3405.30.00.		yes
9.1	Appearance		yes
9.1	Other safety parameters		yes
9.1	Flammability (solid, gas): not relevant, (fluid)	Flammability: this material is combustible, but will not ignite readily	yes
9.1	Explosive limits	Lower and upper explosion limit: 0.6 vol% - 7.6 vol%	yes
9.1	Evaporation rate: Not determined		yes

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Detail King STS+ Paint Sealant

Version number: GHS 3.0

Replaces version of: 2025-11-14 (GHS 2)

Revision: 2025-12-15

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
9.1	Lower explosion limit (LEL): 0.6 vol%		yes
9.1	Upper explosion limit (UEL): 7.6 vol%		yes
9.1		Decomposition temperature: not relevant	yes
9.1		Kinematic viscosity: not determined	yes
9.1		Density and/or relative density	yes
9.1	Vapor density: this information is not available		yes
9.1	Viscosity		yes
9.1	Dynamic viscosity: 55,000 cP at 25 °C		yes
9.1	Explosive properties: none		yes
9.1	Oxidizing properties: none		yes
9.1		Relative vapour density: information on this property is not available	yes
9.1		Information with regard to physical hazard classes: hazard classes acc. to GHS (physical hazards): not relevant	yes
9.1		Other safety characteristics	yes
16		Abbreviations and acronyms: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
Cal ARB	California Air Resources Board
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
ED	Endocrine disruptor

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Detail King STS+ Paint Sealant

Version number: GHS 3.0
Replaces version of: 2025-11-14 (GHS 2)

Revision: 2025-12-15

Abbr.	Descriptions of used abbreviations
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitization
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Detail King STS+ Paint Sealant

Version number: GHS 3.0
Replaces version of: 2025-11-14 (GHS 2)

Revision: 2025-12-15

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapor.
H227	Combustible liquid.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.